CONTACT





Reiss GmbH

Eisleber Str. 5 D – 69469 Weinheim

Fon +49 (0) 6201/25939-0 Fax +49 (0) 6201/25939-10

Email: info@reiss-gmbh.com www.reiss-gmbh.com



OUR PRODUCTS



Sensors

Our sensors measure various disinfectants dissolved in water in diverse applications (swimming pools, drinking water, service water, CIP systems, cooling and waste water etc.). They are offered with various measuring ranges and output signals. We also supply customi-

sed versions of our sensors upon request. Our range of products currently includes the brands described below. They feature a variety of performance profiles and thus can be used for a wide range of applications*

TARAbase, TARAline, TARAtec & TARAsens

Our sensors are subdivided into two groups: Membranecovered sensors and non-membrane-covered sensors. This also allows their use in special applications in areas with high pressures, temperatures and concentrations of the disinfectant

TARAbase TARAline TARAtec TARAsens

* You can find more detailed information about our sensors in our product flyer "Sensors" or on our website.

TARAbase

0Z1

Ozone

membrane-covered sensor

Special features

· short response time

Applications

Swimming-pool, drinking, service and process water

Process conditions

- · no surfactants in the measuring water
- · max. temperature: 45 °C
- · max. pressure: 1 bar

TARAtec

OZ10

Ozone

membrane-covered sensor

Special features

- mechanically robust membrane system
- tolerates surfactants
- · high tolerance to chemicals

Applications

All kinds of water treatment

Process conditions

- max. temperature: 45 °C
- · max. pressure: 1 bar

We also offer sensors for the following disinfectants:

- Chlorine
- Chlorine dioxide
- Peracetic acid

peroxide

acidChloriteHydrogen

Bromine