

	<h1>TARAttec OZ10</h1>										
indicator	ozone										
Application	All kinds of water treatment, also sea water (e. g. bottle washing machine, CIP-plants, rinsler) The membrane system is mechanical resistant. The membrane system is highly resistant to surfactants (tensides).										
Measuring system	Membrane covered, amperometric 2-electrode system										
Electronic	Analog version: <ul style="list-style-type: none"> <li>- voltage output</li> <li>- not galvanically isolated electronics</li> <li>- analog internal data processing</li> <li>- output signal: analog (analog-out/analog)</li> </ul> Digital version: <ul style="list-style-type: none"> <li>- electronic is completely galvanically isolated</li> <li>- digital internal data processing</li> <li>- output signal: analog (analog-out/digital) or digital (digital-out/digital)</li> </ul> mA-version: <ul style="list-style-type: none"> <li>- current output analog</li> <li>- not galvanically isolated electronics</li> <li>- output signal: analog (analog-out/analog)</li> </ul>										
Information about the measuring range of sensors with 4-20 mA	Slope of a sensor can vary production-related or application-related between 65% and 150% of the nominal slope  -> Recommendation to determine the suitable measuring range or the suitable sensor: Concentration to be measured x factor 1.5 = measuring range of the sensor  Example: Concentration to be measured 1.6 ppm x 1.5 = 2.4 -> recommended sensor with a measuring range of 5 ppm										
Accuracy after calibration at repeatability conditions (15°C, pH 7.2 in drinking water) of the upper full scale	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">- Measuring range 2 mg/l:</td> <td style="width: 25%;">at 0.4 mg/l</td> <td style="width: 25%; text-align: right;">&lt;1%</td> </tr> <tr> <td>- Measuring range 20 mg/l:</td> <td>at 4 mg/l</td> <td style="text-align: right;">&lt;1%</td> </tr> <tr> <td></td> <td>at 16 mg/l</td> <td style="text-align: right;">&lt;2%</td> </tr> </table>		- Measuring range 2 mg/l:	at 0.4 mg/l	<1%	- Measuring range 20 mg/l:	at 4 mg/l	<1%		at 16 mg/l	<2%
- Measuring range 2 mg/l:	at 0.4 mg/l	<1%									
- Measuring range 20 mg/l:	at 4 mg/l	<1%									
	at 16 mg/l	<2%									
Working temperature	Measuring water temperature: 0 ... +45 °C (no ice crystals in the measuring water)										
	Ambient temperature: 0 ... +55 °C										
Temperature compensation	Automatically, by an integrated temperature sensor Response time $t_{90}$ = approx. 8 min. Sudden temperature changes must be avoided										
Max. allowed working pressure	Operation without retaining ring: 0.5 bar, no pressure impulses and/or vibrations										
	Operation with retaining ring: 1.0 bar, no pressure impulses and/or vibrations										


	<h1>TARAtec OZ10</h1>
Flow rate	approx. 15-30 l/h in TARAflow FLC, small flow rate dependence is given
pH-range	pH 2 – pH 11
Run-in time	First start-up approx. 3 h
Response time	T <sub>90</sub> : approx. 5 min.
Zero point adjustment	Not necessary
Slope calibration	At the device, by analytical determination, e. g. DPD-4 method (DPD-1 + DPD-3) Advice: when used in sea water DPD-4 method (DPD-1 + DPD-3) is not selective to ozone
interferences	Cl <sub>2</sub> : OZ10H: factor 0.015 OZ10N: negligible ClO <sub>2</sub> : OZ10N: factor 0.06
Absence of the disinfectant	Max. 24 h
Connection	analog-out/analog version: 4-pole plug adapter analog-out/digital version: 4-pole plug adapter digital-out/digital version: 5-pole M12, plug-on flange 4-20 mA version: 2-pole terminal or 5-pole M12, plug-on flange
material	PVC-U, stainless steel 1.4571
Size	diameter: approx. 25 mm Length: analog-out/analog version approx. 175 mm analog-out/digital version approx. 195 mm digital-out/digital version approx. 205 mm 4-20 mA version approx. 220 mm (2-pole-terminal) approx. 190 mm (5-pole-M12)
Transport	+5 ... +50 °C (Sensor, electrolyte, membrane cap)
storage	Sensor: dry and without electrolyte no limit at +5 ... +40 °C
	Electrolyte: in original bottle protected from sunlight at +5 ... +35 °C min. 1 year or until specified EXP-Date
	Membrane cap: in original packing no limit at +5 ... +40 °C (used membrane caps can not be stored)
maintenance	Regularly control of the measuring signal, min. once a week The following specifications depend on the water quality: Change of the membrane cap: once a year Change of the electrolyte: every 3 - 6 months
	EMC-Testing DIN EN 61326-1, 61326-2-3 RoHS compliant

## Technical Data

### 1. OZ10 (Analog output, analog internal signal processing)

analog-out / analog

A potential-free electrical connection is necessary as the sensor electronic is not equipped with a galvanical isolation.


	Measuring range in ppm	Resolution in ppm	Output Output resistance	Nominal slope in mV/ppm	Voltage supply	Connection
OZ10H	0.005...2.000	0.001	0...-2000 mV 1 kΩ	-1000	±5 - ±15 VDC 10 mA	4-pole screw connector
OZ10N	0.05...20.00	0.01		-100		
OZ10HUp	0.005...2.000	0.001	0...+2000 mV 1 kΩ	+1000	10 - 30 VDC 10 mA	
OZ10Up	0.05...20.00	0.01		+100		

(Subject to technical changes!)

### 2. OZ10 (analog output, digital internal signal processing)

analog-out / digital

- The power supply is galvanically isolated inside of the sensor.
- The output signal is galvanically isolated too, that means potential-free.


	Measuring range in ppm	Resolution in ppm	Output Output resistance	Nominal Slope in mV/ppm	Power supply	Connection
OZ10H-An	0.005...2.000	0.001	analog 0...-2 V (max. -2.5 V)	-1000	9-30 VDC approx. 56-20 mA	4-pole screw connector
OZ10N-An	0.05...20.00	0.01	1 kΩ	-100		
OZ10H-Ap	0.005...2.000	0.001	analog 0...+2 V (max. +2.5 V)	+1000		
OZ10N-Ap	0.05...20.00	0.01	1 kΩ	+100		

(Subject to technical changes!)

### 3. OZ10 (digital output, digital internal signal processing)

digital-out / digital

- The power supply is galvanically isolated inside of the sensor.
- The output signal is galvanically isolated too, that means potential-free.

	Measuring range in ppm	Resolution in ppm	Output Output resistance	Power supply	Connection
OZ10H-M0c	0.005...2.000	0.001	Modbus RTU	9-30 VDC	5-pole M12 connector
OZ10N-M0c	0.05...20.00	0.01	There are no terminating resistors in the sensor.	approx. 56-20 mA	


(Subject to technical changes!)

### 4. OZ10 4-20 mA (Analog output, analog internal signal processing)

analog-out / analog


A potential-free electrical connection is necessary as the sensor electronic is not equipped with a galvanical isolation.

#### 4.1 Electrical connection: 2 pole terminal clamp

	Measuring range in ppm	Resolution in ppm	Output Output resistance	Nominal slope in mA/ppm	Voltage supply	Connection
OZ10MA0.5	0.005...0.500	0.001	4...20 mA uncalibrated	32.0	12...30 VDC  R <sub>L</sub> = 50Ω (12V) ... R <sub>L</sub> 900Ω (30V)	2-pole terminal (2 x 1 mm <sup>2</sup> )  Recommended: Round cable ∅ 4 mm 2 x 0.34 mm <sup>2</sup>
OZ10MA2	0.005...2.000	0.001		8.0		
OZ10MA5	0.05...5.00	0.01		3.2		
OZ10MA10	0.05...10.00	0.01		1.6		
OZ10MA20	0.05...20.00	0.01		0.8		

(Subject to technical changes!)

4.2 Electrical connection: 5 pole M12 plug-on flange

	Measuring range	Resolution	Output Output resistance	Nominal slope	Voltage supply	Connection
	in ppm	in ppm		in mA/ppm		
OZ10MA0.5-M12	0.005...0.500	0.001	4...20 mA uncalibrated	32.0	12...30 VDC R <sub>L</sub> = 50Ω (12V) ... R <sub>L</sub> 900Ω (30V)	5-pole M12 plug-on flange  Function of wires: PIN2: +U PIN3: -U
OZ10MA2-M12	0.005...2.000	0.001		8.0		
OZ10MA5-M12	0.05...5.00	0.01		3.2		
OZ10MA10-M12	0.05...10.00	0.01		1.6		
OZ10MA20-M12	0.05...20.00	0.01		0.8		

(Subject to technical changes!)

**Spare Parts**

Type	Membrane cap	Electrolyte	Emery	O-ring
OZ10H	M10.1D O3 mit G-Halter Art. no. 11052.1	EOZ7/W, 100 ml Art. no. 11102	S2 Art. no. 11906	20 x 1.5 silicone Art. no. 11803
OZ10N				
OZ10MA0.5				
OZ10MA2				
OZ10MA5				
OZ10MA10				
OZ10MA20				

(Subject to technical changes!)