

CONTACT

 **Reiss GmbH**
we create sensor solutions



Reiss GmbH

Eisleber Str. 5
D – 69469 Weinheim

Fon +49 (0) 6201/25939-0
Fax +49 (0) 6201/25939-10

Email: info@reiss-gmbh.com
www.reiss-gmbh.com



HYDROGEN PEROXIDE
SENSORS

OUR PRODUCTS



Sensors

Our sensors measure various disinfectants dissolved in water in diverse applications (swimming pools, drinking water, service water, CIP systems, cooling and waste water etc.). They are offered with various measuring ranges and output signals. We also supply customised versions of our sensors upon request. Our range of products currently includes the brands described below. They feature a variety of performance profiles and thus can be used for a wide range of applications*

TARAbase, TARAline, TARAtec & TARAsens

Our sensors are subdivided into two groups: Membrane-covered sensors and non-membrane-covered sensors. This also allows their use in special applications in areas with high pressures, temperatures and concentrations of the disinfectant.

TARAbase



TARAline



TARAtec



TARAsens



* You can find more detailed information about our sensors in our product flyer "Sensors" or on our website.

TARAtec

WP10

Hydrogen peroxide

membrane-covered sensor

Special features

- mechanically robust membrane system
- tolerates surfactants
- high tolerance to chemicals

Applications

All kinds of water treatment

Process conditions

- max. temperature: 45 °C
- max. pressure: 1 bar

We also offer sensors for the following disinfectants:

- Chlorine
- Chlorine dioxide
- Ozone
- Peracetic acid
- Bromine
- Chlorite

